



	Catalog No.	d₁	X	d₂	Colour/Surface
	SM 1753-1	16	X	12	ELSW

AL: Aluminium
Zylinderschrauben DIN 912:
Edelstahl, nichtrostend 1.4301
AL: Aluminium
Socket cap screws DIN 912:
stainless steel 1.4301

ELSW = schwarz eloxiert
anodized black
MT = matt, gleitgeschliffen /
matte, ground

mm



Die Kreuz-Klemmhalter SM 1753-1 verfügen über eine waagrechte und senkrechte Klemmbohrung, beide Klemmbohrungen sind zusätzlich mit einem Vierkant ausgestattet.

Die Klemmschrauben sind in der Standardausführung Zylinderschrauben mit Innensechskant DIN 912. Sie können durch Klemmhebelsets SM 1759-1 ersetzt werden (Bestellbezeichnung siehe Maßtabelle).

The Two-way mounting clamps SM 1753-1 have a horizontal and a vertical clamping bore. Both bores are additionally fitted with a square.

In the standard version, the clamping screws are socket cap screws with hexagonal socket DIN 912. They can be replaced by clamping kits SM 1759-1 (article code see table of dimensions).

d1 = Bohrung für Wellentoleranz h11 / bore for shaft tol. h11
d2 = Bohrung für Wellentoleranz h11 / bore for shaft tol. h11
d3 = Klemmgewinde / clamping thread
s1 = Vierkant / square
s2 = Vierkant / square
Zubehör: empfohlene Klemmhebelsets SM 1759-1 für Klemmgewinde d3 /
Accessory: recommended clamping kits SM 1759-1 für clamping thread d3



d ₁	d ₂	d ₃	k	l ₁	l ₂	m	s ₁	s ₂	SM 1759-1 Zubehör /Accessory für d ₃	kg
∅	∅	∅								
h11	h11									
08	08	M4	14	37	13,5	10	-	-	SM 1759-1M04X14	0,016
10	08	M5	16	46	17	12	V08	-	SM 1759-1M05X16	0,027
10	10						V08	V08	SM 1759-1M05X16	0,025
12	08	M6	20	58	20,5	17	V10	-	SM 1759-1M05X16	0,026
12	12						V10	V10	SM 1759-1M06X20	0,024
15	10						V12	V08	SM 1759-1M06X20	0,051
15	12						V12	V10	SM 1759-1M06X20	0,049
15	15	M6	20	58	20,5	17	V12	V12	SM 1759-1M06X20	0,044
16	12						-	V10	SM 1759-1M06X20	0,048
16	16	M6	20	58	20,5	17	-	-	SM 1759-1M06X20	0,044
20	15						V16	V12	SM 1759-1M06X25	0,080
20	16						V16	-	SM 1759-1M06X25	0,076
20	20						V16	V16	SM 1759-1M06X25	0,067

